

Linux From Scratch - Version 12.1-systemd		
Chapter 9. System Configuration		
	/	
	/etc/inputrc	

9.7.

가 . 가

.

- .
- , 가 bash가

ASCII가 .

- 가
-
- ,

<ll> (: en) <cc> 가 (:

GB) . <charmap> charmap . @euro

Glibc .

```
locale -a
```

Charmaps 가 ISO-8859-1 iso8859-1 (:

iso88591 .

UTF-8 utf8 UTF-8)

가 <locale name>

locale -a (en_GB.iso88591).

```
LC_ALL=<locale name> locale charmap
```

en_GB.iso88591 .

```
ISO-8859-1
```

en_GB.ISO-8859-1 . Bash

가 .

```
LC_ALL=<locale name> locale language
LC_ALL=<locale name> locale charmap
LC_ALL=<locale name> locale int_curr_symbol
LC_ALL=<locale name> locale int_prefix
```

```

, , , , 가
. Glibc . 8

```

```
locale: Cannot set LC_* to default locale: No such file or directory
```

```

localedef
. Glibc 가 가 .
Linux 가
.
Linux
/etc/locale.conf

```

```
cat > /etc/locale.conf << "EOF"
LANG=<ll>_<CC>.<charmap><@modifiers>
EOF
```

```

/bin/bash( " " )
가
/etc
.
/bin/login /etc/passwd
( : [prompt]$/bin/bash). 가
.
/etc/locale.conf 가
/etc/profile' /etc/locale.conf Linux
C.UTF-8 (Linux
).
```

```
cat > /etc/profile << "EOF"
# Begin /etc/profile

for i in $(locale); do
    unset ${i%=*}
done

if [[ "$TERM" = linux ]]; then
    export LANG=C.UTF-8
else
    source /etc/locale.conf

```

```
for i in $(locale); do
    key=${i%=*}
    if [[ -v $key ]]; then
        export $key
    fi
done
fi

# End /etc/profile
EOF
```

systemd **localectl**

localectl

/etc/locale.conf

```
localectl set-locale LANG="<ll>_<CC>.<charmap><@modifiers>"
```


locale

LANG, LC_CTYPE, LC_NUMERIC

. LANG en_US.UTF-8

LC_CTYPE en_US

```
localectl set-locale LANG="en_US.UTF-8" LC_CTYPE="en_US"
```

 **localectl**

systemd

LFS

C() en_US() . C US-ASCII 7

Is 가

Mutt Pine

8-bit). 8 RFC 가 (unknown

From:
<https://www.gamu.kr/dokuwiki/> -

Permanent link:
https://www.gamu.kr/dokuwiki/linuxfromscratch/12.1/160-configuring_the_system_locale

Last update: 2024/06/15 13:18

